

CB3 High plastic palletbox - 1200 x 1000 mm - with funnel base and slide valve - on 2 skids





Transoplast +31(0)314 66 44 00 website@transoplast.com dev.transoplast.com

Product specifications

Weight (kg)	57 kg
External dimensions (L x W x H)	1200 × 1000 × 1140 mm
Temperature range	-30°C to +40°C
Capacity	850 liter
Color	Grey
Material	HDPE
Bottom	Closed, reinforced with central bottom discharge
Sidewalls	Closed
Max. load capacity per box	1000 kg
Max. static stacking load	4000 kg
Max. dynamic stacking load	1200 kg
Internal dimensions (L x W x H)	1108 × 897 × 960 mm

Properties

Dimensions: 1200 x 1000 x 1140 mm.

Capacity: 850 liters.

Material: Plastic.

Funnel Bottom: Tapered bottom with a central outlet.

Opening: Central opening of 120x120 mm, adjustable to 140 x 140 mm or 240x240 mm.

Slide Valve: Manually operated from the short side to close the opening.

Interior: Smooth, funnel-shaped interior, optimized for controlled dispensing.

Application: Ideal for dry bulk goods such as granulate, seeds, grain, dry animal feed, pellets, and other small components.

Bottom: Sloped at a 35-degree angle for easy flow out without tipping.

Suitability for Food: Suitable for use with food products.

Limitations: Not suitable for liquids and moist products, unless used with a plastic liner.

Maximum Load Capacity: 1000 kg.



Transoplast +31(0)314 66 44 00 website@transoplast.com dev.transoplast.com

Description

The CB3 High pallet container with funnel bottom measures 1200 x 1000 x 1140 mm and has a capacity of 850 liters. This extra tall plastic pallet box is equipped with a central outlet at the bottom of the box. In the lower part of the box, a tapered funnel bottom is welded in with a central opening of 120x120 mm, which can be adjusted as desired. This opening is closed by a slide valve that can be manually operated from the short side of the box.

The CB3 High box, with its smooth, funnel-shaped interior, is ideal for controlled dispensing of dry bulk goods such as granules, seeds, grain, dry animal feed, pellets, and other small components. Thanks to the sloped bottom at a 35-degree angle, the product easily flows out when the slide valve is opened, without the need for tipping and dumping.

The container is also suitable for use with food products. It is important to note that this pallet box is not suitable for liquids and moist products unless it is used with a plastic liner. The maximum loading capacity per box is 1000 kg.



Matching accessories



Alternatieve artikelen







Transoplast +31(0)314 66 44 00 website@transoplast.com dev.transoplast.com