



Euro pallet - H1 L - 1200 x 800 mm - ESD version (with rims - underside open)



Product specifications

Weight (kg)	17,5 kg
External dimensions (L x W x H)	1200 x 800 x 157 mm
Temperature range	-30°C to +40°C, briefly up to +90°C
Color	Black
Material	PP with carbon compound
Surface resistance	10 ⁹ ohms (according to DIN 53428 / IEC 60093)
Static load capacity	5000 kg
Edge height	7 mm
Dynamic load capacity	1000 kg
Load capacity in racks	850 kg

Properties

Electrostatically dissipative (ESD): protects sensitive components against charging up and electrostatic discharge

Raised rims around the H1 prevent the load sliding off and mutual sliding of empty pallets

H1 is extra strong due to oblique connection between the runners and the chocks

Description

Euro pallet type H1-L (1200 x 800 x H 157 mm) ESD version: electrically conductive plastic. Equipped with 3 pallet runners longitudinally, underside blocks, and open pallet runners. With raised edges all around (7 mm). Static load capacity is 5000 kg, dynamic 1000 kg, and in pallet racking 850 kg. Surface resistance: <10⁹ Ohm (according to DIN 53428 / IEC 60093). The H1-L is made of antistatic and conductive plastic.

