

Article number: 83222201

Bedrukking mogelijk



Industrial pallet - CS3 L - 1200 x 1000 mm - ESD version - with rims - open runners



Product specifications

Uitwendig (LxBxH)	1200 x 1000 x 150 mm
Dynamic load capacity	1000 kg kg
Material	HDPE with carbon compound
Article number	83222201
Weight (kg)	15,2 kg
Temperature range	-30°C to +40°C, briefly up to +90°C
Color	Black
Surface resistance	10 ⁷ ohms (according to DIN 53428 / IEC 60093)
Static load capacity	5000 kg kg
Edge height	7 mm mm
Load capacity in racks	400 kg

Properties

Electrostatically dissipative (ESD): protects sensitive components against charging up and electrostatic discharge

Raised rims around the pallet prevent the load sliding off and mutual sliding of empty pallets

Description

Industrial pallet type CS3-L (1200 x 1000 x H 150 mm) ESD version: electrically conductive plastic. Equipped with 3 longitudinal pallet runners, bottom blocks, and open pallet runners. With raised edges all around (7 mm). Static load capacity is 5000 kg, dynamic 1000 kg, and in pallet racks 400 kg. Surface resistance: 10^6 Ohm (according to DIN 53428 / IEC 60093). The CS3-L is made of antistatic and conductive plastic.



Alternatieve artikelen

