



Industrial pallet - D3 - 1200 x 1000 mm (with rims)



Product specifications

Uitwendig (LxBxH)	1200 x 1000 x 150 mm
Dynamic load capacity	1000 kg kg
Material	HDPE
Article number	83315701
Weight (kg)	14 kg
Temperature range	-30°C to +40°C, briefly up to +90°C
Color	Brown
Static load capacity	5000 kg kg
Edge height	7 mm mm
Load capacity in racks	400 kg

Properties

High load capacity that is upgradable to 1000 kg in pallet racks using reinforcing sections: on request

RFID technology is straightforward to integrate into the pallet, even later on. The RFID tag holder provides durable protection against external influences.

All openings in the pallet surface go right through so are easy to clean

D3 runners are chamfered on both edges.

Raised rims around the D3 prevent the load sliding off and mutual sliding of empty pallets

D3 is extra strong due to oblique connection between the runners and the chocks

Description

Plastic Industrial Pallet D3 (1200 x 1000 x H 150 mm) - food-grade. With three longitudinal runners. The underside of the pallet feet is open, the underside of the runners is ribbed. The plastic ISO pallet is equipped with a 7 mm perimeter edge. A variant with a 22 mm edge is available on request (see "Options"). Static load capacity is 5000 kg, dynamic 1000 kg, and in pallet racking 400 kg. The load capacity in pallet racking can be increased to 1250 kg with reinforcement profiles; even afterwards. This allows the plastic pallet to cover a very wide range of applications.

