

Industrial pallet - D3-5 ECO - 1200 x 1000 mm (with rims)







Product specifications

Weight (kg)	15 kg
External dimensions (L x W x H)	1200 × 1000 × 150 mm
Temperature range	-30°C to +40°C, briefly up to +90°C
Color	Black
Material	Recycled ECO-HDPE
Static load capacity	5000 kg
Edge height	7 mm
Dynamic load capacity	1000 kg
Load capacity in racks	400 kg

Properties

High load capacity that is upgradable to 1000 kg in pallet racks using reinforcing sections: on request

RFID technology is straightforward to integrate into the pallet, even later on. The RFID tag holder provides durable protection against external influences.

All openings in the pallet surface go right through so are easy to clean

D3 runners are chamfered on both edges.

Raised rims around the D3 prevent the load sliding off and mutual sliding of empty pallets

D3 is extra strong due to oblique connection between the runners and the chocks

Description

Industrial pallet / block pallet type D3-5 ECO (1200 x 1000 x H 150 mm) made of ECO regranulate. Equipped with 5 pallet runners (3 longitudinally, 2 transversely), underside blocks, and open pallet runners (ribbed). With raised edges all around (7 mm). Static load capacity is 5000 kg, dynamic 1000 kg, and in pallet racking 400 kg. The load capacity can be upgraded upon request to 1250 kg in racking.

