

Artikelnummer: 83182222

Bedrukking mogelijk



# Industrial pallet - H3 L - 1200 x 1000 mm - ESD version (with rims - underside open)



## Product specifications

Weight (kg)	21,5 kg
External dimensions ( L x W x H)	1200 x 1000 x 160 mm
Temperature range	-30°C to +40°C, briefly up to +90°C
Color	Black
Material	PP with carbon compound
Surface resistance	10 <sup>9</sup> ohms (according to DIN 53428 / IEC 60093)
Static load capacity	5000 kg
Edge height	7 mm
Dynamic load capacity	1250 kg
Load capacity in racks	850 kg

## Properties

**Electrostatically dissipative (ESD):** protects sensitive components against charging up and electrostatic discharge

**Raised rims around the H3** prevent the load sliding off and mutual sliding of empty pallets

**H3 is extra strong** due to oblique connection between the runners and the chocks

## Description

Industrial pallet / block pallet type H3-L (1200 x 1000 x H 160 mm) ESD version: electrically conductive plastic. Equipped with 3 pallet runners longitudinally, underside blocks, and open pallet runners. With raised edges all around (7 mm). Static load capacity is 5000 kg, dynamic 1250 kg, and in pallet racking 850 kg. Surface resistance: <10<sup>9</sup> Ohm (according to DIN 53428 / IEC 60093). The H3-L is made of antistatic and conductive plastic.



Alternatieve artikelen

