



Industrial pallet - TC3-5 - 1200 x 1000 mm (with rims)



Product specifications

Uitwendig (LxBxH)	1200 x 1000 x 160 mm
Dynamic load capacity	1500 kg kg
Material	HDPE
Article number	87030840
Weight (kg)	22,5 kg
Temperature range	-30°C to +40°C, briefly up to +90°C
Color	Grey
Static load capacity	7500 kg kg
Edge height	7 mm mm
Load capacity in racks	1250 kg

Properties

TC pallets runners are chamfered on both edges

Connections of the pallet chocks to the runners and the pallet surface are extra reinforced. Breakage at these sensitive points is thus reduced to a minimum

Intelligent design of the pallet chock ensures better grip of wrapping and stretch film

The TC pallet's patented weld geometry guarantees a high load capacity and long lifetime

Top and bottom pallet surface are completely smooth and unperforated without external rib structures

Very high load capacity that is upgradable to 1750 kg in pallet racks using reinforcing sections: on request

Raised rims around the TC3-5 prevent the load sliding off and mutual sliding of empty pallets

Description

Industrial pallet type TC3-5 (1200 x 1000 x H 160 mm) - suitable for foodstuffs. Equipped with 5 pallet runners (3 lengthwise, 2 crosswise), closed bottom blocks, and runners with reinforcement ribs. With raised edges all around (7 mm). Also available with extra high edge (22 mm; see "Options"). Top and bottom pallet deck are completely smooth and closed without external rib structures. Temperature resistance: -30°C to +40°C, short-term up to +90°C. Static load capacity is 7500 kg, dynamic 1500 kg, and in pallet racks 1250 kg. With optional reinforcement profiles in the deck, the load capacity in pallet racks can even be increased to 2000 kg.

