



Industrial pallet - TC3 ECO - 1200 x 1000 mm (with rims)



Product specifications

Weight (kg)	21,5 kg
External dimensions (L x W x H)	1200 x 1000 x 160 mm
Temperature range	-30°C to +40°C, briefly up to +90°C
Color	Black
Material	Recycled ECO-HDPE
Static load capacity	7500 kg
Dynamic load capacity	1250 kg
Load capacity in racks	1000 kg

Properties

TC pallets runners are chamfered on both edges

Connections of the pallet chocks to the runners and the pallet surface are extra reinforced. Breakage at these sensitive points is thus reduced to a minimum

Intelligent design of the pallet chock ensures better grip of wrapping and stretch film

Raised rims around the TC3 prevent the load sliding off and mutual sliding of empty pallets

The TC pallet's patented weld geometry guarantees a high load capacity and long lifetime

Top and bottom pallet surface are completely smooth and unperforated without external rib structures

Very high load capacity that is upgradable to 1750 kg in pallet racks using reinforcing sections: on request

Description

Industrial pallet type TC3 ECO (1200 x 1000 x H 160 mm) made of ECO regranulate. Equipped with 3 pallet runners lengthwise, closed bottom blocks, and runners with reinforcement ribs. With raised edges all around (7 mm), also available with extra high edge (22 mm; see "Options"). Top and bottom pallet deck of the TC3 are completely smooth and closed without external rib structures. Static load capacity is 7500 kg, dynamic 1500 kg, and in pallet racks 1000 kg. With optional reinforcement profiles in the deck, the load capacity in pallet racks can even be increased to 1750 kg.

Alternatieve artikelen

