

Plastic palletbox MaxiLog - 1200 x 1000 mm - on 3 skids - Grey - Perforated







Product specifications

Weight (kg)	30,9 kg
External dimensions (L x W x H)	1200 × 1000 × 760 mm
Temperature range	-30°C to +70°C
Capacity	610 liter
Color	Grey
Material	HDPE
Bottom	Perforated
Sidewalls	Perforated
Colorcode	RAL 7040
Max. load capacity per box	450 kg
Max. static stacking load	4500 kg
Max. dynamic	
stacking load	1000 kg
•	1000 kg
stacking load	
stacking load Surface Load capacity	Perforated

Properties

Versatile transport solution for food and bulk goods.

Reinforced base for minimal deformation.

UN-approved versions available for dangerous goods.

Stackable design with corner stacking features for safe storage.

Smooth, easy-to-clean surfaces.

Compatible with automated handling systems.

Robust and sturdy, designed for industrial processing.

Fully recyclable at the end of its long service life.

SmartLink technology option for tracking and tracing.

Available in solid or ventilated versions, with 4 feet, 2 or 3 runners.



Description

The MaxiLog 1200x1000x760 - with 3 runners, Ventilated pallet box is an ideal solution for transporting food or large-volume bulk goods. The reinforced base design minimizes base deformation, ensuring product integrity.

The pallet box can be stacked up to 10 units high, providing efficient storage and transport. Smooth surfaces make the box easy to clean and hygienic for use. It is available in both solid and ventilated versions, with 4 feet, 2 or 3 runners. UN-approved versions are also available for transporting dangerous goods by road, sea, and air.



