

SB3 plastic palletbox - perforated -1200 x 1000 mm - with funnel base and slide valve - on 2 runners







Product specifications

Weight (kg)	55 kg
External dimensions (L x W x H)	1200 × 1000 × 790 mm
Temperature range	-30°C to +40°C
Capacity	500 liter
Color	Grey
Material	HDPE
Bottom	Reinforced with central bottom discharge
Sidewalls	Perforated
Sidewalls Max. load capacity per box	Perforated 700 kg
Max. load capacity per	
Max. load capacity per box Max. static stacking	700 kg
Max. load capacity per box Max. static stacking load Max. dynamic stacking	700 kg 5000 kg 1200 kg

Properties

Type: Perforated SB3 palletbox **Function: funnel bottom** Dimensions: 1200 x 1000 x H 790 mm Capacity: 500 liters Material: standard plastic Bottom outlet: centrally located in the base of the pallet box



Description

The **perforated pallet box with a hopper bottom** from Transoplast is a versatile storage and transport solution, specifically designed for the controlled dispensing of dry bulk goods such as granulate, seeds, grain, pellets, and animal feed. This pallet box (dimensions: 1200 x 1000 x H 790 mm, capacity: 500 liters) features a unique funnel-shaped bottom with a central opening of 120x120 mm, easily operated with a sliding gate. This allows goods to be unloaded without tipping, saving both time and effort.

The perforated walls provide excellent airflow and moisture regulation, making them ideal for products that require ventilation. This pallet box is perfect for dry bulk materials and can also be used for moist products or food items with a plastic inliner. With a maximum load capacity of 700 kg, the pallet box is both robust and efficient, suitable for intensive use in various industries such as agriculture, food processing, and logistics.



Alternatieve artikelen



